


















iSea Group



















TEMPWRIST	TEMPFACE	FLOORSTAND
<p>Main Terminal</p> <ul style="list-style-type: none">● Realtime Temperature and Face Mask Alerts● Abnormal Body Temperature Alert● 7 inch Touchscreen● Local offline recognition supported● Facial Detection time within 0.2 second● Web Interface and PC Software <p>Wrist Temperature Module</p> <ul style="list-style-type: none">● Touchless Detection from Wrist● Temperature Range 86°F to 113°F● Measurement Deviation ≤ 0.9°F● Measurement Distance: 3/8 inch to 1-1/2 inch <p>Floor Stand</p> <ul style="list-style-type: none">● 45.6" x 4.7" x 1.1" Stand● 11.0" x 8.7" Base● Stainless Steel● Weight 15 lb	<ul style="list-style-type: none">● Realtime Temperature and Face Mask Alerts● Abnormal Body Temperature Alert● Forehead Temperature Module and 7 inch Touchscreen● Local offline recognition supported● Detect face and measure temperature within 0.2s● Temperature Range 86°F to 113°F● Measurement Deviation ≤ 0.9°F● Measurement Distance: 1 to 6 ft● Temperature Measurement Version PC Software	<ul style="list-style-type: none">● Floor Stand for LTK3607FM-T or LTK3607FM● 52.8" x 8.9" x 3.9" Stand● 4 bolts securing the stand to the ground● SPCC Steel● Weight 14.8 lb.● Power, network and data wires included and pre-fished● Optional wiring holes on its back and bottom
\$	\$	\$








M2-C	D2-WIFI	M2-C-2WIRE	D2-WIFI-2WIRE	PD-2WIRE	INDOORDESK
					
IP Door Station Module	IP Indoor Station	2-Wire Door Station Module	2-Wire Indoor Station	2-Wire Power Distributor	Indoor Station Desk Stand
\$	\$	\$	\$	\$	\$

M2-DIS	M2-KP	M2-6B	M2-COVER	M2-MCR	M2-IM	M2-BK
						
LED Display Module	Keypad Module	6 Button Nametag Module	Cover for Unused Buttons	Mifare Card Reader Module	Indicator Module	Blank Module
\$	\$	\$	\$	\$	\$	\$









M2-1S	M2-2S	M2-3S	M2-1F	M2-2F	M2-3F	M2-CABLE
						
Surface Mount, 1 Module	Surface Mount, 2 Module	Surface Mount, 3 Module	Flush Mount, 1 Module	Flush Mount, 2 Module	Flush Mount, 3 Module	Spare RS485 Cable
\$	\$	\$	\$	\$	\$	\$

<p>R29S</p> 	<p>R29S-F/R29S-S/ R29S-COVER</p> 	<p>R20A</p> 
<ul style="list-style-type: none"> • Multi-Apartment Outdoor Station • 7" Touchscreen with Card Reader • SIP Integration and Cloud Option • Mounting Brackets Sold Separately 	<ul style="list-style-type: none"> • Brackets for R29S • IN-WALL (Flush Mount) • ON-WALL (Surface Mount) • Additional Rain Cover Available 	<ul style="list-style-type: none"> • Single Apartment Outdoor Station • 1 Call Button and Card Reader • SIP Integration and Cloud Option • Surface Mount Bracket Included
\$	\$	\$
<p>C313S/C313W</p> 	<p>C313-DESK</p> 	<p>ACL2DOOR/ACL4DOOR</p> 
<ul style="list-style-type: none"> • Akuvox Video Indoor Station • 7" Touchscreen with PoE • Wi-Fi Available on AK-C313W • Surface Mount Included 	<ul style="list-style-type: none"> • Desk Stand for AK-C313S/W • White Color, Metal Construction • Indoor Station not included 	<ul style="list-style-type: none"> • LTS 2 / 4 Door Controller • Secure Metal Closure with Lock • Supports 4 Wiegand 26/34 bit Readers • Up to 10,000 Cards and 50,000 Events • Build-in 12VDC 8.5A Power Supply • Add X-VMS Server for APP Access • UL Listed
\$	\$	\$
<p>ACL1DOOR01</p> 	<p>ACL1DOOR02</p> 	<p>ACL1DOOR03</p> 
<ul style="list-style-type: none"> • LTS 1 Door Card Terminal • Must use Mifare Card / Fob for Entry • Keypad for Programming Only • Indoor Use • Plastic Housing 	<ul style="list-style-type: none"> • LTS 1 Door Card Terminal with Code • Mifare or EM Cards / Fobs Supported • Keypad for Programming and Entry with Code • IP 65 Outdoor • IK10 Vandal Proof, Metal Housing 	<ul style="list-style-type: none"> • LTS 1 Door Card Terminal with Fingerprint • Support Mifare Cards / Fobs and Fingerprint • Program by Scanning Enrollment Cards • IP 65 Outdoor • IK10 Vandal Proof, Metal Housing
\$	\$	\$

							
ACL-CR-01	ACL-CR-01K	ACL-CR-02	ACL-CR-02K	ACL-CR-03	ACL-CR-03K	ACL-CR-04	ACL-CR-04K
<ul style="list-style-type: none">• LTS Slim Mifare Classic Reader• 8 or 10 Digit Selectable (via Wire)• IP 65 Weatherproof• UL Listed• Surface Mount		<ul style="list-style-type: none">• LTS Slim Mifare Classic Reader• 8 or 10 Digit Selectable (via DIP)• IP 65 Weatherproof• UL Listed• Surface Mount		<ul style="list-style-type: none">• LTS Mifare Classic Reader• 8 or 10 Digit Selectable (via DIP)• IP 65 Weatherproof• 1 Gang			
\$	\$	\$	\$	\$	\$	\$	\$

						
ACL-CR-05	ACL-CR-05K	ACL-ISSUER	ACL-CARD	ACL-KEYFOB	ACL-KEYFOB2	ACL-WATCHBAND
<ul style="list-style-type: none">• LTS Vandel Proof Mifare Reader• 8 or 10 Digit Selectable (via DIP)• IP 65 Weatherproof, IK10, Metal• UL Listed• Surface Mount, 1 Gang		<ul style="list-style-type: none">• LTKE100ME• LTS USB Card/Fob Issuer• Supports NVMS Software• Supports X-VMS Web Client• UL Listed		<ul style="list-style-type: none">• LTS Mifare Card / Slim Key Fob / Round Key Fob / Watchband• 13.56 Mifare Classic• 8 Digit and 10 Digit # Printed		
\$	\$	\$	\$	\$	\$	\$

						
ACLDS-201	ACLDS-202	ACLML-206	ACLML-212	ML-206D	ACLML-212D	ACLMS-201
<ul style="list-style-type: none"> • LTS Electrical Strike NC/NO Adjustable • Build-in LBM • DC 12V Only • Cylindrical Latch Only 		<ul style="list-style-type: none"> • LTS UL Listed Single/Double Door Maglock • DC 12V or DC 24V, UL Listed, 600lb / 1200lb Holding Force • For Inward Swinging Doors, Use LTKLBLZ06(C)/LTKLBLZ12/LTKLBLZ06D(C) LZ Bracket Bracket • For Frameless Glass Doors, Use LTKLBU06 Ride-on Bracket 				<ul style="list-style-type: none"> • LTS Motion RTE Motion Sensor • SPST, NC Only, DC12V • -W white and -B Black • Wide Angle Activation Range
\$		\$	\$	\$	\$	\$

							
ACLPB-01	ACLPB-01LED	ACLPB-02	ACLPB-03LED	ACLPB-04LED	ACLPB-05	ALCPB-06	ACLPB-07
<ul style="list-style-type: none"> • LTS Exit Button • SPST (NO only) • 1 Gang 	<ul style="list-style-type: none"> • LTS 1 Gang LED Exit • SPDT(NO/NC) • 1 Gang 	<ul style="list-style-type: none"> • LTS 1 Gang Exit • SPDT(NO/NC) • 1 Gang 	<ul style="list-style-type: none"> • LTS1 Gang LED Exit • SPST (NO only) • 1 Gang 	<ul style="list-style-type: none"> • LTSTouchlessExit • SPDT(NO/NC) • 1 Gang, 1-25s Timer 	<ul style="list-style-type: none"> • LTS Exit Button • Aluminum Alloy • 3.39" x 3.39" x 0.79" 	<ul style="list-style-type: none"> • LTS Exit Button • Aluminum Alloy • 3.54" x 1.38" x 1.14" 	<ul style="list-style-type: none"> • LTS Touchless Exit • Aluminum Alloy • 3.39" x 1.97" x 1.34"
\$	\$	\$	\$	\$	\$	\$	\$



iSea Group Inc

☎ 1(585)978-3888

✉ Customerservice@iseagroup.org