



iSea Group

Professional Level

Image		 4kH.265⁺	 4kH.265⁺	 4kH.265⁺		
Price		\$	\$	\$	\$	\$
Model Number		IPN-4P4	IPN-8P8-N	IPN-8P8	IPN-16P16-N	IPN-16P16
Video Input		All CH IP@40Mbps	All CH IP@80Mbps		All CH IP@160Mbps	
Record	2MP	All CH@30fps/CH	All CH@30fps/CH		All CH@30fps/CH	
	4MP	All CH@20fps/CH	All CH@20fps/CH	All CH@30fps/CH	All CH@20fps/CH	All CH@30fps/CH
	8MP	All CH@15fps/CH	All CH@15fps/CH	All CH@20fps/CH	All CH@15fps/CH	All CH@20fps/CH
Video Output		HDMI up to 4K or VGA up to 1080P		HDMI up to 4K and VGA up to 1080P	HDMI up to 4K or VGA up to 1080P	HDMI up to 4K and VGA up to 1080P
Recording Resolution		Up to 4K, 8 MegaPixels (3840x2160)				
Decoding Format		H.265/H.265+/H.264/H.264+				
Decoding Capability		1CH@4K / 4CH@1080P		2CH@4K / 8CH@1080P	1CH@4K / 4CH@1080P	2CH@4K / 8CH@1080P
Playback Resolution		Up to 4K, 8 MegaPixels (3840x2160)				
Audio In/Out		1CH/1CH, RCA				
Alarm In/Out		-		4/1	-	4/1
Built-in PoE		4CH	8CH		16CH	
Network		10/100/1000M, 1 RJ45				
Storage		1 SATA up to 6TB, NAS, IP SAN	2 SATA up to 12TB, NAS, IP SAN			
Support Fisheye Camera#		-				
Support POS#		-				
Dimensions		12.4"(W)x9.1"(D)x1.8"(H)	15"(W)x12.4"(D)x1.8"(H)			
USB Compatibility		2 USB 2.0		1 USB 2.0, 1 USB 3.0	2 USB 2.0	1 USB 2.0, 1 USB 3.0

Enterprise Level

Image					
					
Price		\$	\$	\$	\$
Model Number		IPN-16	IPN-16P16	IPN-32	IPN-32P16
Video Input		All CH IP@160Mbps		All CH IP@256Mbps	
Record	2MP	All CH@30fps/CH		All CH@30fps/CH	
	4MP	All CH@30fps/CH		All CH@30fps/CH	
	8MP	All CH@20fps/CH		All CH@20fps/CH	
Video Output		HDMI up to 4K(3840x2160) and VGA up to 1920x1080P and CVBS up to 704x480			
Recording Resolution		Up to 12 MegaPixels (4000x3072)			
Decoding Format		H.265/H.265+/H.264/H.264+			
Decoding Capability		4CH@4K / 16CH@1080P			
Playback Resolution		Up to 12 MegaPixels (4000x3072)			
Audio In/Out		1CH/1CH, RCA			
Alarm In/Out		16/4			
Built-in PoE		-	16CH	-	16CH
Network		10/100/1000M, 2 RJ45	10/100/1000M, 1 RJ45	10/100/1000M, 2 RJ45	10/100/1000M, 1 RJ45
Storage		4 SATA up to 32TB, eSATA, NAS, IP SAN			
Support Fisheye Camera#		8			
Support POS#		4 (TCP or RS232)		8 (TCP or RS232)	
Dimensions		17.5"(W)x15.3"(D)x2.8"(H)			
USB Compatibility		2 USB 2.0, 1 USB 3.0, eSATA, DVD-RW			

Enterprise Level

Image		 	 	 	 
Price		\$	\$	\$	\$
Model Number		IPN-32-R	IPN-64-R	IPN-32-R8	IPN-256-R16
Video Input		All CH IP@320Mbps	All CH IP@320Mbps	All CH IP@256Mbps	All CH IP@768Mbps
Record	2MP	All CH@30fps/CH	All CH@30fps/CH	All CH@30fps/CH	All CH@15fps
	4MP	All CH@30fps/CH	All CH@20fps/CH	All CH@30fps/CH	All CH@10fps
	8MP	All CH@20fps/CH	All CH@15fps/CH	All CH@15fps/CH	All CH@4fps
Video Output		HDMI1 up to 4K(3840x2160) or VGA1 up to 2K(2560x1440) and HDMI2/VGA2 up to 1920x1080P		HDMI1 up to 4K(3840x2160) or VGA1 up to 2K(2560x1440) and HDMI2 or VGA2 up to 1920x1080P and CVBS up to 704x480	HDMI1 and HDMI2 up to 4K(4096x2160) VGA up to 1920x1080P and Built-in 7" Touch Screen LCD, 6 HDMI TV Wall
Recording Resolution		Up to 12 MegaPixels (4000x3072)			
Decoding Format		H.265/H.265+/H.264/H.264+			
Decoding Capability		4CH@4K / 16CH@1080P		2CH@4K / 8CH@1080P	5CH@4K / 20CH@1080P
Playback Resolution		Up to 12 MegaPixels (4000x3072)			
Audio In/Out		1CH/2CH, RCA			1CH/1CH, RCA
Alarm In/Out		16/4			16/8
Built-in PoE		-			
Network		10/100/1000M, 2 RJ45			10/100/1000M, 4 RJ45, 4 Fiber Optic
Storage		8 SATA up to 64TB, eSATA, NAS, IP SAN RAID 0, 1, 5, 6, and 10, Hot Swap			16 SATA up to 128TB, NAS, IPSAN RAID 0, 1, 5, 6 and 10, Hot Swap
Support Fisheye Camera#		8			16
Support POS#		8 (TCP or RS232)		16 (TCP)	
Dimensions		17.5"(W)x18.5"(D)x3.5"(H)			17.5" (W)×19.4"(D)× 5.7"(H)
USB Compatibility		2 USB 2.0, 1 USB 3.0, eSATA			2 USB 2.0, 2 USB 3.0

Hybrid and Wi-Fi Solutions

Image		 	 	 
Price		\$	\$	\$
Model Number		IPH-4	IPH-8	IPH-16
Video Input		All CH IP(40Mbps) + All CH TVI3.0	All CH IP(80Mbps) + All CH TVI3.0	All CH IP(72Mbps) + All CH TVI3.0
Record	2MP	All CH IP@30fps + All CH TVI 3MP@15fps	All CH IP@30fps + All CH TVI 3MP@15fps	All CH IP@30fps + All CH TVI 3MP@15fps
	4MP	All CH IP@20fps + All CH TVI 3MP@15fps	All CH IP@20fps + All CH TVI 3MP@15fps	All CH IP@15fps + All CH TVI 3MP@15fps
	8MP	All CH IP@15fps + All CH TVI 3MP@15fps	All CH IP@15fps + All CH TVI 3MP@15fps	All CH IP@10fps + All CH TVI 3MP@15fps
Video Output		VGA or HDMI up to 1920x1080P and CVBS up to 704x480		
Recording Resolution		Up to 5 MegaPixels (2560x1920)		
Decoding Format		H.264/H.264+		
Decoding Capability		4CH	8CH	16CH
Playback Resolution		Up to 5 MegaPixels (2560x1920)		
Audio In/Out		4CH/1CH, RCA		
Alarm In/Out		4CH/1CH	8CH/4CH	16CH/4CH
Network		10/100/1000M, 1 RJ45		
Storage		1 SATA up to 6TB, NAS, IP SAN	2 SATA up to 12TB, NAS, IP SAN	
Support Fisheye Camera#		-		
Support POS#		1 (TCP)	2 (TCP)	
Dimensions		12.4"(W)x9.1"(D)x1.8"(H)	15"(W)x12.4"(D)x1.8"(H)	
USB Compatibility		2 USB 2.0	1 USB 2.0, 1 USB 3.0	

IP Dome Camera



Key Features

- 2 - 4 Megapixel Resolution
- Support H.264 Zip+, H.264
- Micro SD/SDHC/SDXC Card Slot up to 128GB
- Video Content Analytics
- ANR (Automatic Network Replenishment)
- 3-Axis
- IP67, IK10 Vandal-Proof
- 3D DNR, BLC
- DC 12V, PoE
- UL Listed



IRD-228RD-WIFI	IRD-428RW-WIFI	IRD-228RD	IRD-240RD
• 2MP • 12 IR up to 70ft • 2.8mm Fixed Lens • 1920 x 1080P@30fps • DWDR • Built-in Wi-Fi	• 4MP • 30 IR up to 100ft • 2.8mm Fixed Lens • 2688 x 1520P@20fps • True WDR 120dB • Built-in Wi-Fi	• 2MP • 12 IR up to 70ft • 2.8mm Fixed Lens • 1920 x 1080P@30fps • DWDR • Special Design for Wide FoV	• 2MP • 30 IR up to 100ft • 4mm Fixed Lens • 1920 x 1080P@30fps • DWDR
\$	\$	\$	\$

DJ-01	DJ-02	DLWM	DPM-01	LWM-DM	VPM	CMT
Junction Box(White/Black)	Ceiling Mount	Wall Mount(White/Black)	Pendant Mount	Wall mount	Pole Mount	Corner Mount
\$	\$	\$	\$	\$	\$	\$

IP Dome Camera



Key Features

- Advanced Compression H.265/ H.265+
- Matrix IR LED up to 100ft
- Micro SD/SDHC/SDXC Card Slot up to 128GB
- True WDR 120dB
- Video Content Analytics
- ANR (Automatic Network Replenishment)
- IP67, IK10 Vandal Proof
- 3D DNR, BLC
- DC 12V, PoE
- UL Listed

4k

IRD-828MW	IRD-840MW	IRD-628MW	IRD-640MW
• 8.3MP/4K • 2.8mm Fixed Lens • 3840 × 2160@15fps	• 8.3MP/4K • 4mm Fixed Lens • 3840 × 2160@15fps	• 6.3MP • 2.8mm Fixed Lens • 3072 × 2048@20fps	• 6.3MP • 4mm Fixed Lens • 3072 × 2048@20fps
\$	\$	\$	\$
IRD-428MW		IRD-440MW	
• 4.1MP • 2.8mm Fixed Lens • 2688 × 1520@30fps • 0.018 Lux @ F1.6		• 4.1MP • 4mm Fixed Lens • 2688 × 1520@30fps • 0.018 Lux @ F1.6	
\$		\$	

DJ-01	DJ-02	DLWM	DPM-01	LWM-DM	VPM	CMT
						
Junction Box	Inclined ceiling mount	Wall Mount	Pendant Mount	Wall mount	Vertical pole mount	Corner Mount
\$	\$	\$	\$	\$	\$	\$

IP Dome Camera



Key Features

- Advanced Compression H.265/ H.265+
- Matrix IR LED up to 100ft
- Motorized Lens with Smart Focus
- Micro SD/SDHC/SDXC Card Slot up to 128GB
- True WDR 120dB
- 3.5mm Audio Jack I/O, Alarm I/O
- Video Content Analytics
- ANR (Automatic Network Replenishment)
- IP67, IK10 Vandal Proof
- 3D DNR, BLC
- DC 12V, PoE
- UL Listed
- Junction Box included

4k

IHD-412MW-M	IHD-812MW-M	IHD-612MW-M
• 4MP • 2.8 - 12 mm VF Motorized Lens • 3072 × 2048@20fps • 0.018 Lux @ F1.6	• 8.3MP/4K • 2.8 - 12 mm VF Motorized Lens • 3840 × 2160@15fps • 0.018 Lux @ F1.6	• 6.3MP • 2.8 - 12 mm VF Motorized Lens • 3072 × 2048@20fps • 0.018 Lux @ F1.6
\$	\$	\$

DPM-02	LWM-HD	VPM-N	CMT-N
			
Pendant mount	Wall mount	Vertical pole mount	Corner mount
\$	\$	\$	\$

IP Turret Camera



Key Features

- 2 - 4 Megapixel Resolution
- Support H.264 Zip+, H.264
- Matrix IR LED up to 100ft
- Video Content Analytics
- IP67
- 3D DNR, BLC
- DC 12V, PoE
- UL Listed

IRT-228MD-B/TRT-228MD	IRT-240MD-B/IRT-240MD	IRT-428MD/IRT-440MD
• 2MP • 2.8mm Fixed Lens • 1920 x 1080P@30fps • DWDR	• 2MP • 4mm Fixed Lens • 1920 x 1080P@30fps • DWDR	• 4MP • 2.8mm Fixed Lens/4mm Fixed Lens • 2688 x 1520P@20fps • DWDR
\$	\$	\$
IRT-428MW-B	IRT-440MW-B	IRT-460MW-B
• 4MP • 2.8mm Fixed Lens • 2688 x 1520P@20fps • True WDR 120dB	• 4MP • 4mm Fixed Lens • 2688 x 1520P@20fps • True WDR 120dB	• 4MP • 6mm Fixed Lens • 2688 x 1520P@20fps • True WDR 120dB
\$	\$	\$

TJ-01	TJ-02	LWM-TR	TPM	VPM	CMT
					
Junction Box	Junction Box	Wall Mount	Pendant mount	Pole Mount	Corner Mount
\$	\$	\$	\$	\$	\$

IP Turret Camera



4k

4k

Key Features

- Advanced Compression H.265 / H.265+
- Matrix IR LED up to 100ft
- Micro SD/SDHC/SDXC Card Slot up to 128GB
- True WDR 120dB
- Video Content Analytics
- ANR (Automatic Network Replenishment)
- IP67 Water Proof
- 3D DNR, BLC
- DC 12V, PoE, UL Listed

IRT-828MW	IRT-840MW	IRT-628MW	IRT-640MW
• 8.3MP/4K • 2.8mm Fixed Lens • 3840 × 2160@15fps	• 8.3MP/4K • 4mm Fixed Lens • 3840 × 2160@15fps	• 6.3MP • 2.8mm Fixed Lens • 3072 × 2048@20fps	• 6.3MP • 4mm Fixed Lens • 3072 × 2048@20fps
\$	\$	\$	\$
IRT-428MW	IRT-440MW	IRT-228MW	IRT-240MW
• 4.1MP • 2.8mm Fixed Lens • 2688 × 1520@30fps • 0.018 Lux @ F1.6	• 4.1MP • 4mm Fixed Lens • 2688 × 1520@30fps • 0.018 Lux @ F1.6	• 2.1MP • 2.8mm Fixed Lens • 1920 × 1080@30fps	• 2.1MP • 4mm Fixed Lens • 1920 × 1080@30fps
\$	\$	\$	\$

TJ-01	TJ-02	LWM-TR	TPM	VPM	CMT
Junction Box	Junction Box	Wall Mount	Pendant Mount	Vertical pole mount	Corner Mount
\$	\$	\$	\$	\$	\$

IP Turret Camera



4k

Key Features

- Advanced Compression H.265/ H.265+
- Matrix IR LED up to 100ft
- Motorized Lens with Smart Focus
- Micro SD/SDHC/SDXC Card Slot up to 128GB
- True WDR 120dB
- 3.5mm Audio Jack I/O, Alarm I/O
- Video Content Analytics
- ANR (Automatic Network Replenishment)
- IP67, IK10 Vandal Proof
- 3D DNR, BLC
- DC 12V, PoEnt
- UL Listed
- Junction Box included

IHT-812MW-M

- 8.3MP/4K
- 2.8 - 12 mm VF Motorized Lens
- 3840 × 2160@15fps
- 0.018 Lux @ F1.6

\$

IHT-612MW-M

- 6.3MP
- 2.8 - 12 mm VF Motorized Lens
- 3072 × 2048@20fps
- 0.018 Lux @ F1.6

\$

HVPM



Vertical pole mount

\$

HCMT



Corner mount

\$

IP Bullet Camera



Key Features

- Advanced Compression H.265/H.265+ (On Models B, C, D, E)
- Matrix IR LED up to 100ft
- MicroSD/SDHC/SDXC Card Slot up to 128GB (On Models B, C, D, E)
- True WDR 120dB (On Models B, C, D, E)
- Video Content Analytics
- ANR (Automatic Network Replenishment)
- IP67
- 3D DNR, BLC
- DC 12V, PoE
- UL Listed
- 3 Year Warranty

IMB-240MW-WIFI		IMB-240MW	IMB-228MW
• 2MP • 4mm Fixed Lens • 1920 x 1080P@30fps • H.264 • Built-in Wi-Fi		• 2MP • 4mm Fixed Lens • 1920 x 1080p@30fps	• 4MP • 2.8mm Fixed Lens • 2688 x 1520@30fps • 0.018 Lux @ F1.6 • White or Black Housing
\$		\$	\$
IMB-440MW		IMB-628MW/IMB-640MW	
• 4MP • 4mm Fixed Lens • 2688 x 1520@30fps • 0.018 Lux @ F1.6		• 6MP • 2.8mm/4mm Fixed Lens • 3072 x 2048@20fps	
\$		\$	
UJB-01		UJB-01B	
			
Universal Junction Box		Universal Junction Box	
\$		\$	

IP Bullet Camera



Key Features

- Advanced Compression H.265/ H.265+
- Matrix IR LED up to 165ft
- Micro SD/SDHC/SDXC Card Slot up to 128GB
- True WDR 120dB
- Video Content Analytics
- ANR (Automatic Network Replenishment)
- IP67
- 3D DNR, BLC
- DC 12V, PoE
- UL Listed

4k

IRB-828MW	IRB-840MW	IRB-628MW
• 8.3MP/4K • 2.8mm Fixed Lens • 3840 × 2160@15fps	• 8.3MP/4K • 4mm Fixed Lens • 3840 × 2160@15fps	• 6.3MP • 2.8mm Fixed Lens • 3072 × 2048@20fps
\$	\$	\$
IRB-640MW	IRB-428MW	IRB-440MW
• 6.3MP • 4mm Fixed Lens • 3072 × 2048@20fps	• 4.1MP • 2.8mm Fixed Lens • 2688 × 1520@30fps • 0.018 Lux @ F1.6	• 4.1MP • 4mm Fixed Lens • 2688 × 1520@30fps • 0.018 Lux @ F1.6
\$	\$	\$

VPM	CMT
	
Pole Mount	Corner Mount
\$	\$

IP Bullet Camera



4k

Key Features

- Advanced Compression H.265 / H.265+
- Matrix IR LED up to 165ft
- Micro SD/SDHC/SDXC Card Slot up to 128GB
- True WDR 120dB
- 3.5mm Audio Jack I/O, Alarm I/O
- Video Content Analytics
- ANR (Automatic Network Replenishment)
- IP67, IK10 Vandal Proof
- 3D DNR, BLC
- DC 12V, PoE
- UL Listed
- Junction Box Included

IHB-812MW-M	IHB-612MW-M	IHB-412MW-M
• 8.3MP • 2.8 - 12 mm VF Motorized Lens • 3840 × 2160@15fpsfps • 0.018 Lux @ F1.6	• 6.3MP • 2.8 - 12 mm VF Motorized Lens • 3072 × 2048@20fps • 0.018 Lux @ F1.6	• 4.1MP • 2.8 - 12 mm VF Motorized Lens • 2688 × 1520@30fps • 0.018 Lux @ F1.6
\$	\$	\$

VPM-N	CMT-N
Vertical pole mount	Corner mount
\$	\$

IP Turret Camera



Key Features

- Advanced Compression H.265/ H.265+
- IR LED up to 100ft
- IP67
- DWDR
- 3D DNR, BLC
- DC 12V, PoE
- Metal Housing

IRT-428MD-N

- 3.7MP
- 2.8mm Fixed Lens
- 1/3" CMOS
- 2560 × 1440@20fps

\$

TJ-01	LWM-TR	VPM	CMT
Junction Box	Wall Mount	Pole Mount	Corner Mount
\$	\$	\$	\$

IP Dome Camera



Key Features

- Advanced Compression H.265/ H.265+
- IR LED up to 100ft
- IP67, IK10 Vandal-Proof
- DWDR
- 3D DNR, BLC
- DC 12V, PoE
- Metal Housing

IRD-428RD-N

- 3.7MP
- 2.8mm Fixed Lens
- 1/3" CMOS
- 2560 × 1440@20fps

\$

DJ-01	DJ-02	DLWM	LWM-DM	DPM-01	VPM	CMT
Junction Box	Ceiling Mount	Wall Mount	Wall Mount	Pendant Mount	Pole Mount	Corner Mount
\$	\$	\$	\$	\$	\$	\$

IP Turret Camera



Key Features

- Varifocal Motorized Lens
- Support H.264 Zip+, H.264
- IR LED up to 100ft
- IP67
- True WDR 120dB
- 3D DNR, BLCE
- DC 12V, PoE
- Metal Housing

IRT-412MW-NM

- 3.7MP
- 2.8 - 12 mm VF Motorized Lens
- 1/3" CMOS
- 2688 × 1520@20fps

\$

TJ-02	LWM-TR	VPM	CMT
			
Junction Box	Wall Mount	Pole Mount	Corner Mount
\$	\$	\$	\$

IP Motorized Lens Dome Camera



Key Features

- Advanced Compression H.265/ H.265+
- Varifocal Motorized Lens
- Micro SD/SDHC/SDXC Card Slot up to 128GB
- IR LED up to 100ft
- IP67, IK10 Vandal-Proof
- True WDR 120dB
- 3D DNR, BLC
- DC 12V, PoE
- Metal Housing

IPD-412MW-NW

- 3.7MP
- 2.8 - 12 mm VF Motorized Lens
- 1/3" CMOS
- 2560 × 1440@20fps

\$

DJ-03	LWM-MD	LWM-MDB	DPM-02	VPM	CMT
					
Junction Box	Wall Mount	Wall Mount	Pendant mount	Pole Mount	Corner Mount
\$	\$	\$	\$	\$	\$

IP Turret Camera



Key Features

- Advanced Compression H.265/ H.265+
- IR LED up to 100ft
- IP67
- DWDR
- 3D DNR, BLC
- DC 12V, PoE
- Metal Housing

IMB-228MD-N	IMB-428MD-N	UJB-01
• 2.1MP • 2.8mm Fixed Lens • 1/2.8" CMOS • 1920×1080@30fps • DWDR	• 3.7MP • 2.8mm Fixed Lens • 1/3" CMOS • 2560×1440@20fps • DWDR	
		Universal Junction Box
\$	\$	\$

IP Dome Camera



Key Features

- Advanced Compression H.265/ H.265+
- Varifocal Motorized Lens
- Micro SD/SDHC/SDXC Card Slot up to 128GB
- IR LEDs up to 100ft
- IP67
- True WDR 120dB
- 3D DNR, BLC
- DC 12V, PoE
- Metal Housing

IPB-412MW-NW

- 3.7MP
- 2.8 - 12 mm VF Motorized Lens
- 1/3" CMOS
- 2560 × 1440@20fps

\$159

BJ-02	VPM	CMT
		
Junction Box	Pole Mount	Corner Mount
\$	\$	\$



IDB-2180DR

- 2MP
- 180° Panoramic View
- 1920x1080P
- IR up to 15ft
- Two-Way Audio
- 16VAC - 24VAC
- Built-in Wi-Fi
- DWDR, DNR
- Micro SD Card up to 128GB

\$



ICB-428MW-WIFI

- 4MP
- Supports H.264/ H.264 ZIP+
- 2.8mm Fixed Lens
- 2688 x 1520P@20fps
- True WDR 120dB
- IR up to 33ft
- Micro SD/SDHC/SDXC Card Slot up to 128GB
- Alarm I/O
- Built-in Microphone & Speakert
- Indoor

\$

IP Dome Camera



Key Features

- Advanced Compression H.265/H.265+
- Matrix IR LED up to 33ft
- MicroSD/SDHC/SDXC Card Slot up to 128GB
- Built-in Microphone
- Audio and Alarm I/O
- True WDR 120dB
- Video Content Analytics
- ANR (Automatic Network Replinishehmt)
- IP66, IK8 Vandal Proof
- 3D DNR, BLC
- DC 12V, PoE
- UL Listed
- 3 Year Warranty

IMD-428MW-A	IMD-428MW-WIFI-A	IMD-628MW-A
• 4MP • 2.8mm Fixed Lens • 2688 x 1520@30fps • 0.018 Lux @ F1.6	• 4MP • 2.8mm Fixed Lens • 2688 x 1520@30fps • 0.018 Lux @ F1.6 • Built-in Wi-Fi	• 6MP • 2.8mm Fixed Lens • 3072 x 2048@20fps
\$	\$	\$

License Plate IP Camera



ILP-220LW-M	ILP-232RW-M
• 2MP • 8 - 20mm VF Motorized Lens • 1920 x 1080P@30fps • White Flux LED	• 2MP • 8 - 32mm Auto Focus Motorized Lens • 1920 x 1080P@60fps • 0.0027 Lux @ F1.4 • Up to 60MPH • License Plate Recognition • Infrared IR
\$	\$

Fisheye IP Camera



Key Features

- 6 & 12 Megapixel Resolution
- 360° Fisheye and 180° Panoramic View
- Multiple Viewing Modes and Virtual PTZ
- Support H.264 Zip+, H.264
- Micro SD/SDHC/SDXC Card Slot up to 128GB
- Video Content Analytics
- Heat Map for Motion Analytics
- Low-light, IR up to 33ft
- IP66, IK10 Vandal-Proof
- Built-in Microphone and Speaker
- DWDR
- DC12V, PoE
- UL Listed

IFE-6-A	IFE-12-A
• Fisheye IP Camera • 6MP • 1.27mm Fixed Lens • 3072 x 2048@25fps	• Fisheye IP Camera • 12MP • 1.98mm Fixed Lens • 4000 x 3072@25fps • Audio I/O, Alarm I/O
\$	\$

LWM-FE	FCM	FJ-01
Wall Mount	Ceiling Mount	Inclined Ceiling/Wall Mount
\$	\$	\$

Long Range IP Bullet Camera		
	Key Features • 4 x Matrix IR LED up to 394ft • 20x Optical Zoom Motorized Lens with Auto Focus • Up to 60fps • Support H.264 Zip+, H.264 • Micro SD/SDHC/SDXC Card Slot up to 128GB • Video Content Analytics • ANR (Automatic Network Replenishment) • Audio I/O, Alarm I/O • True WDR 120dB • IP67 • HLC • 3D DNR, BLC • DC12V, PoE • UL Listed	IRB-294MW-M
		• 2MP • 4.7 - 94mm VF Motorized Lens • Ultra-Low Light • 1920 × 1080 up to 60fps
		\$
IP Dome Camera		
	Key Features • 2MP In-Ceiling IP Camera • 4mm Fixed Lens • 1920 x 1080p @ 30fps • H.264 • Video Content Analytics • MicroSD Card Slot up to 64GB • Snap-On No Screw Installation • UL Listed • 3 Year Warranty	ICC-240D
		• 2MP • 1/3" CMOS • 1920X1080P@30fps • 4mm Fixed Lens • 3D DNR, DWDR, BLC, VCA • Micro SD/SDHC/SDXC Card Slot • DC 12V, PoE
		\$



Key Features

- 4 Physical Cameras in 1 Housing
- Save Labor with Multi-Lens by Using Just 1 Ethernet Cable
- 4 Adjustable Viewing Angle Cameras with Motorized Lens

IPC-812RW-M

- 4 x 2MP Flexible Lens (8MP)
- 2.8 - 12mm Motorized Lens
- 1920 x 1080P@30fps
- Advanced Compression H.265/H.265+
- True WDR 120dB
- MicroSD Card Slot up to 128GB
- Audio & Alarm In and Out
- IP67, IK10
- 3 Year Warranty

\$

IPC-2012RW-M

- 4 x 5MP Flexible Lens (20MP)
- 2.8 - 12mm Motorized Lens
- 2560 x 1920P@24fps
- Advanced Compression H.265/H.265+
- True WDR 120dB
- MicroSD Card Slot up to 128GB
- Audio & Alarm In and Out
- IP67, IK10
- 3 Year Warranty

\$

IP PTZ Camera



Key Features

- Outdoor/ Indoor
- 1/3" CMOS
- 0.005Lux@F1.6 Ultra Low Light
- 2.8 - 12mm
- 4x Optical Zoom, Auto Focus
- H.265/H.265+/H.264/H.264+
- IR LEDs up to 66ft, Auto Intensity Adjustment
- 0° to 90°(Auto-flip)
- True WDR 120dB, 3D DNR, HLC, BLC, EIS
- Two Way Audio
- Micro SD Card Slot up to 256GB, ANR
- IK10 Vandal-Proof, IP66, Lightning/Surge Protection
- DC 12V, PoE (802.3 af) Max 12W
- 2.5" (Φ)

ISPTZ-212WR

- 2.1MP, Full HD 1080P
- 1920x1080P@30fps

\$

ISPTZ-412WR

- 4MP High Definition
- 2560x1440P@25fps

\$



Key Features

- 1/2.8" CMOS
- 20x Optical Zoom
- 4.7-94mm
- 3D Zoom
- Schedule Task
- Audio I/O, Alarm I/O
- True Day/Night
- 3D DNR, DWDR
- 3D Privacy Masking
- PoE Plus, AC 24V
- 2MP, Full HD 1080P
- 1920x1080P@30fps
- 4" (Φ)



IPTZ-294

- Indoor/Outdoor
- IP66
- Wall Mount Bracket Included

\$

IPTZ-294-C

- Ceiling & Flush Mount
- Indoor

\$



Key Features

- 1/2.8" CMOS
- Auto IR Intensity Adjustment
- 3D Zoom
- Schedule Task
- IP66
- Audio I/O, Alarm I/O
- True Day/Night
- 3D DNR, DWDR
- 3D Privacy Masking
- PoE Plus, AC 24V
- Wall Mount Bracket Included
- 2MP, Full HD 1080P
- 1920x1080P@30fps



IPTZ-294R-B

- 20x Optical Zoom
- High PoE, AC 24V
- BNC Output
- 4.7-94mm
- 4 Matrix IR LEDs@492ft
- 5" (Φ)

\$

IPTZ-2129R

- 30x Optical Zoom
- High PoE, AC 24V
- 6" (Φ)
- 4.3-129mm
- 6 IR LEDs@394ft

\$

IP PTZ Cameras



Key Features

- 0.005Lux@F1.6 Ultra Low Light
- H.265/H.265+/H.264/H.264+
- IR LEDs up to 164ft, Auto Intensity Adjustment
- Smart Tracking
- -5° to 90°(Auto-flip)
- True WDR 120dB, 3D DNR, HLC, BLC, Defog, EIS
- Audio I/O, Alarm I/O
- Micro SD Card Slot up to 256GB, ANR
- IK10 Vandal-Proof, IP66, Lightning/Surge Protection
- DC 12V, PoE+(802.3 at, class4), Max 18W
- 4" (Φ)

IMPTZ-275WR-T

- 2.1MP, Full HD 1080P
- 1/2.8" CMOS
- 1920x1080P@30fps
- 5 - 75mm
- 15x Optical Zoom, Auto Focus



IMPTZ-2120WR-T

- 2.1MP, Full HD 1080P
- 1/2.8" CMOS
- 1920x1080P@30fps
- 4.8 - 120mm
- 25x Optical Zoom, Auto Focus



IMPTZ-4120WR-T

- 4MP High Definition
- 1/2.5" CMOS
- 2560x1440@30fps
- 4.8 - 120mm
- 25x Optical Zoom, Auto Focus



Key Features

- 2.1MP, Full HD 1080P
- 1/2.8" CMOS
- 1920x1080P@60fps
- H.265/H.265+/H.264/H.264+
- IR LEDs up to 492ft, Auto Intensity Adjustment
- Audio I/O, Alarm I/O
- Micro SD Card Slot up to 256GB, ANR
- IP66, Lightning Protection, Surge Protection
- 7" (Φ)

IPTZ-2153WR-T

- 0.005Lux@F1.6 Ultra Low Light
- 4.8 - 153mm
- 32x Optical Zoom, Auto Focus
- Smart Tracking
- -15° to 90°(Auto-flip)
- True WDR 120dB, 3D DNR, HLC, BLC, Defog, EIS
- AC 24V, High PoE Max 40W



IPTZ-2120WR-T

- 0.002Lux@F1.2 Ultra DarkSight
- 4.8 - 120mm
- 25x Optical Zoom, Auto Focus
- Smart Tracking 2.0
- Human/Vehicle/Object Detection powered by Deep Learning
- -10° to 90°(Auto-flip)
- 120dB Ture WDR, 3D DNR, HLC, BLC, Defog, EIS
- AC 24V(Max 50W), High PoE(Max 60W)



HD-TVI PTZ Camera



Key Features

- 23x Optical Zoom, 4-92mm
- 1/3" CMOS
- True Day/Night, 3D DNR, DWDR
- 3D Privacy Masking
- 256 Preset Positions
- 2MP, Full HD 1080P
- 1920x1080P@30fps
- 4 Patterns, 8 Patrols
- Self-adaptive, RS485 Pelco D/Pelco P
- CVBS Output
- AC 24V
- 4" (Φ)



TPTZ-292

TPTZ-292-C

- IP66
- Wall Mount Bracket Included
- Indoor/Outdoor

- Ceiling & Flush Mount
- Indoor

\$

\$



Key Features

- 1/3" CMOS
- TrueDay/Night,3DDNR,DWDR
- 3D Privacy Masking
- 256 Preset Positions
- 4 Patterns, 8 Patrols
- Self-adaptive, RS485 Pelco D/Pelco P
- IP66,Indoor/Outdoor
- AC 24V
- Wall Mount Bracket Included
- 5" (Φ)

TPTZ-2120MW-B

- 2MP, Full HD 1080P
- 1920X1080P @30fps
- 30x Optical Zoom, 4-120mm
- 4 Matrix IR LEDs@492ft
- CVBS Output

\$

PTZ Keyboard		
Image		
Connection Type	KBT	KBI
	RS485	USB
Compatible Model	TVI PTZ and some of the IP PTZ	IP/TVI PTZ
Price	\$	\$

SPWM	PWM	MPWM	PCM	PPM
				
Wall Mount for ISPTZ	Wall Mount	Wall Mount for IMPTZ	PTZ Corner Mount	PTZ Pole Mount
\$	\$	\$	\$	\$
SPPM-01	SPPM-02	MPPM-01	MPPM-02	PPWM
				
Pendant Mount 7.8" for ISPTZ	pendant mount 78" for ISPTZ	Pendant Mount 7.8" for IMPTZ	Pendant Mount 20" for IMPTZ	Parapet Wall Mount
\$	\$	\$	\$	\$

HD-TVI DVRs

Image				
				
Price	\$	\$	\$	\$
Model Number	T2D-4	T2D-8N	T2D-8	T2D-16
Analog Video Input	4CH (TVI3.0/AHD/CVI/960H) Channel 1 up to 4MP	8CH (TVI3.0/AHD/CVI/960H) Channel 1&2 up to 4MP		16CH (TVI3.0/AHD/CVI/960H) Channel 1-4 up to 4MP
Record Rate	1080P@15fps CH 1 up to 4MP@20fps	1080P@15fps CH 1&2 up to 4MP@20fps		1080P@15fps CH 1-4 up to 4MP@20fps
IPC Input	1CH up to 4MP@20fps	2CH up to 4MP@20fps		
Decoding Format	H.265 / H.265+ / H.264 / H.264+			
Video Output	VGA or HDMI up to 1920x1080p, and CVBS			HDMI up to 3840x2160, and VGA up to 1080p, and CVBS
Playback Channel	4CH	8CH		16CH
Audio In/Out	1CH/1CH, RCA			
Alarm In/Out	-			
Network	10/100Mbps			10/100/1000Mbps
Storage	1 SATA up to 6TB, NAS, IP SAN		2 SATA up to 12TB, NAS, IP SAN	
eSata	-			
USB	2, USB 2.0			1 USB 2.0, 1 USB 3.0
PTZ	1 RS485			
Support Pos#	-			
Product Dimensions	12.4"(W)x9.1"(D)x1.8"(H)		15"(W)x12.4"(D)x1.8"(H)	

HD-TVI DVRs

Image				
Price	\$	\$	\$	\$
Model Number	T2D-24	T2D-32	T2D-24P	T2D-32P
Analog Video Input	24CH (HD-TVI 2.0)	32CH (HD-TVI 2.0)	24CH (HD-TVI 2.0)	32CH (HD-TVI 2.0)
Record Rate	1080P@15fps, 720P@30fps			
IPC Input	8CH up to 1080P@30fps		16CH up to 1080P@30fps	
Decoding Format	H.264/H.264+			
Video Output	VGA or HDMI up to 1080p		VGA or HDMI1,and HDMI 2 UP TO 1080P	
Playback Channel	24CH	32CH	24CH	32CH
Audio In/Out	4CH/1CH, RCA		16CH/1CH, RCA	
Alarm In/Out	16/4		16/8	
Network	10/100/1000Mbps		10/100/1000Mbps, 2 RJ45	
Storage	4 SATA up to 32TB, NAS, IP SAN		8 SATA up to 64TB, NAS, IP SAN	
eSata	1			
USB	3, USB 2.0			
PTZ	1 RS485			
Support Pos#	8 (TCP)		16 (TCP)	
Product Dimensions	17.5"(W)x15.3"(D)x2.8"(H)		17.5"(W)x18.5"(D)x3.5"(H)	

HD-TVI DVRs

Image	 5-1 H.265⁺ 5-1 4k H.265⁺		 5-1 4k H.265⁺
Price	\$		\$
Model Number	T5D-4		T5D-8
Analog Video Input	4CH (HD-TVI/4.0/AHD/CVI/960H)		16CH (HD-TVI4.0/AHD/CVI/960H)
Record Rate	5MP@12fps, 4MP@15fps, 3MP@18fps 1080P@30fps		8MP@8fps, 5MP@12fps, 4MP@15fps, 3MP@18fps 1080P@30fps
IPC Input	2CH, Up to 6MP (3072x2048)		
Decoding Format	H.265 / H.265+ / H.264 / H.264+		
Video Output	VGA or HDMI up to 1080p, and CVBS		HDMI up to 3840x2160, or VGA up to 1080p, and CVBS
Playback Channel	4CH		16CH
Audio In/Out	4CH/1CH, RCA		
Alarm In/Out	4/1		16/4
Network	10/100/1000Mbps		
Storage	1 SATA up to 10TB, NAS, IP SAN		2 SATA up to 20TB, NAS, IP SAN
USB	2, USB 2.0		1 USB 2.0, 1 USB 3.0
PTZ	1 RS485		
Support Pos#	-		2 (TCP)
Product Dimensions	12.4"(W)x9.1"(D)x1.8"(H)		15"(W)x12.4"(D)x1.8"(H)

HD-TVI DVRs

Image	 5-14kH.265⁺	 5-14kH.265⁺	 5-14kH.265⁺
Price	\$	\$	\$
Model Number	T5D-24	T5D-32	T5D-32P
Analog Video Input	24CH (HD-TVI4.0/AHD/CVI/960H)	32CH (HD-TVI4.0/AHD/CVI/960H)	
Record Rate	8MP@8fps, 5MP@12fps, 4MP@15fps, 3MP@18fps, 1080P@30fps		
IPC Input	8CH up to 4K/8MP (3840x2160) adjustable up to 32CH	8CH up to 4K/8MP (3840x2160) adjustable up to 40CH	32CH up to 12MP (3840x2160) adjustable up to 64CH
Decoding Format	H.265 / H.265+ / H.264 / H.264+		
Video Output	VGA or HDMI1 up to 1920x1080p, and HDMI2 up to 3840x2160, and CVBS		
Playback Channel	16CH		
Audio In/Out	4CH/1CH, RCA		16CH/2CH, RCA
Alarm In/Out	16/4		16/8
Network	10/100/1000Mbps, 2 RJ45		
Storage	4 SATA up to 40TB, NAS, IP SAN, RAID 0 1, 5, 6, and 10 Hot Swap		8 SATA up to 80TB,NAS, IP SAN, RAID 0 1,5, 6 and 10 Hot Swap
eSata	1		
USB	2 USB2.0/1 USB3.0		
PTZ	RS-232, RS-485 (full-duplex), Keyboard		
Support Pos#	8 (TCP or RS232)		
Product Dimensions	17.5"(W)x15.3"(D)x2.8"(H)		17.4"(W)x18.5"(D)x3.5"(H)

HD-TVI Fisheye Camera			
TFE-5A • 5MP HD-TVI Fisheye Camera • 1.1mm Fixed Lens • 2592 x 1944@12.5fps • 0.01 Lux @f/1.2, 0 Lux with IR • 3 Matrix IR 2.0 up to 65ft (20m) • Built-in Microphone • 1 Channel Audio Output • UTC Control to OSD Menu • DC 12V 	FWM		FCM
			
	Wall Mount		Ceiling Mount
	\$		\$
	FPM-01		FPM-02
			
	Pendant Mount 7.8" (20cm)		Pendant Mount 78" (200cm)
	\$		\$
HD-TVI CAMERAS		HD-TVI Dome Camera	HD-TVI Bullet Camera
			
TRT-8135MD-M	TRD-8135MD-M	TRD-836MD	TMB-828MD
• 8.3MP 4K UHD • 2.7-13.5mm VF Motorized Lens w/Auto Focus • 3840x2160@12.5fps • 0.01 Lux, Smart IR • 2 Matrix IR 2.0 131ft • TVI/AHD/CVI/960H • IP67	• 8.3MP 4K UHD • 2.7-13.5mm V-F Motorized Lens w/Auto Focus • 3840x2160@12.5fps • 0.01 Lux, Smart IR • 2 Matrix IR 2.0 LED up to 131ft • TVI/AHD/CVI/960H Switchable • IP67, IK10	• 8.3MP 4K UHD • 3.6mm Fixed Lens • 3840x2160@12.5fps • 0.01 Lux, Smart IR • Matrix IR up to 65ft • TVI/AHD/CVI/960H Switchable • IP67, IK10	• 8.3MP 4K UHD • 2.8mm Fixed Lens • 3840x2160@12.5fps • 0.01 Lux, Smart IR • Matrix IR up to 65ft • TVI/AHD/CVI/960H Switchable • IP67
\$	\$	\$	\$

HD-TVI Turret Camera



Key Features

- High Definition Turret HD-TVI Camera
- 2 Matrix IR 2.0 LED up to 131ft
- UTC Control to OSD Menu
- DC 12V

TRT-228MW/TRT-236MW	TRT-228MW-S/TRT-240MW-S	TRT-528MD-S	
• 2MP • 2.8mm/3.6mm Fixed Lens • 1920×1080P@30fps • 0.01 Lux, Smart IR • True WDR 120dB • IP66	• 2MP Ultra Low Light • 2.8mm Fixed Lens • 1920x1080@30fps • 0.005 Lux@F2.0 • True WDR 120dB • IP67	• 5MP Ultra Low Light • 2.8mm Fixed Lens • 2560x1944@20fps • 0.008 Lux@F1.2 • IP67	
\$	\$	\$	

 Key Features • High Definition Turret HD-TVI Camera • 1 Matrix IR LED up to 131ft • UTC Control to OSD Menu • 0.01 Lux, Smart IR • IP66 • DC 12V	TPT-228MD/TPT-228MD-B/TPT-236MD	TPT-228MW/TPT-236MW
	• 2MP • 2.8/3.6mm Fixed Lens • 1920×1080P@30fps	• 2MP • 2.8/3.6mm Fixed Lens • 1920×1080P@30fps • True WDR 120dB
	\$	\$

TJ-01	TJ-02	LWM-TR	TPM	VPM	CMT
					
Junction Box	Junction Box	Wall Mount	Pendant mount	Pole Mount	Corner Mount
\$	\$	\$	\$	\$	\$

HD-TVI Turret Camera



Key Features

- High Definition Turret HD-TVI Camera
- 2 Matrix IR 2.0 LED up to 65ft
- UTC Control to OSD Menu
- IP67
- DC 12V

TMT-228MW/TMT-236MW

- 2MP Ultra Low Light
- 2.8/3.6mm Fixed Lens
- 1920x1080@30fps
- 0.005 Lux@F2.0
- True WDR 120dB

\$

TMT-528MD/TMT-536MD

- 5MP
- 2.8/3.6mm Fixed Lens
- 2560x1944@20fps
- 0.01Lux, Smart IR

\$

Key Features

- High Definition Turret HD-TVI Camera
- 2MP
- 1920x1080P@30fps
- 24 IR LEDs up to 65ft
- UTC Control to OSD Menu
- IP66
- DC 12V



TMT-228RD(-B)/TMT-236RD(-B)

- 2MP
- 2.8/3.6mm Fixed Lens
- Housing option (White/Black)

\$

LWM-MT



Wall Mount

\$

VPM



Pole Mount

\$

CMT



Corner Mount

\$

UJB-01



Universal Junction Box

\$

UJB-01B



Universal Junction Box

\$

HD-TVI Turret Camera



Key Features

- High Definition Turret HD-TVI Camera
- 2.8-12mm Varifocal Motorized Lens
- UTC Control to OSD Menu
- DC 12V



TRT-212MW-M	TRT-212MW-MS	TRT-512MW-M
• 2MP • 1920x1080@30fps • 0.01 Lux, Smart IR • 6 Matrix IR LED up to 131ft • True WDR 120dB • IP66	• 2MP Ultra Low Light • 1920x1080@30fps • 0.005 Lux@F1.8 • 6 Matrix IR LED up to 131ft • True WDR 120dB • Auto focus • IP67	• 5MP • 2560x1944@20fps • 0.01Lux, Smart IR • 2 Matrix IR LED up to 131ft • IP67
\$	\$	\$

TJ-02	LWM-TR	VPM	CMT
Junction Box	Wall Mount	Pole Mount	Corner Mount
\$	\$	\$	\$

HD-TVI Dome Camera



Key Features

- High Definition Dome HD-TVI Camera
- 2 Matrix IR 2.0 LED up to 65ft
- IK10 Vandal-Proof Dome
- 3-Axis Easy Installation
- UTC Control to OSD Menu
- IP67
- DC 12V

TRD-228MW-S	TRD-528MW	TRD-528MW-S
• 2MP Ultra Low Light • 2.8mm Fixed Lens • 1920x1080@30fps • 0.005 Lux@F2.0 • True WDR 120dB	• 5MP • 2.8mm Fixed Lens • 2560x1944@20fps • 0.01 Lux, Smart IR	• 5MP Ultra Low Light • 2.8mm Fixed Lens • 2560x1944@20fps • 0.008 Lux@F1.2
\$	\$	\$

Key Features



- High Definition Dome HD-TVI Camera
- 1920×1080P@30fps
- 18 IR LEDs up to 65ft
- IK10 Vandal-Proof Dome
- 3-Axis Easy Installation
- UTC Control to OSD Menu
- IP66
- DC 12V
- Housing option (White/Black)

TRD-228RD-(B)

- 2MP
- 2.8mm Fixed Lens
- AoV 105.8°

\$

TRD-236RD-(B)

- 2MP
- 3.6mm Fixed Lens
- AoV 84.3°

\$

DJ-01	DJ-02	DLWM	VPM	VPM	LWM-DM
					
Junction Box (White/Black)	Ceiling Mount	Wall Mount (White/Black)	Pole Mount	Corner Mount	Wall Mount
\$	\$	\$	\$	\$	\$

HD-TVI Dome Camera



Key Features

- High Definition Dome HD-TVI Camera
- 2MP
- 1920×1080P@30fps
- 2.8-12mm Varifocal Lens
- 24 IR LEDs up to 131ft
- IK10 Vandal-Proof Dome
- 3-Axis Easy Installation
- UTC Control to OSD Menu
- IP66



Key Features

- High Definition Dome HD-TVI Camera
- 2.8-12mm Varifocal Motorized Lens
- 2 Matrix IR 2.0 LED up to 131ft
- IK10 Vandal-Proof Dome
- 3-Axis Easy Installation
- UTC Control to OSD Menu
- IP67
- DC 12V, AC 24V

TRD-212RD	TRD-212RW	TRD-212MW-MS	TRD-512MW-M
• DC 12V, AC 24V	• DC 12V, AC 24V • True WDR 120dB • CVBS Output	• 2MP Ultra Low Light • 1920x1080@30fps • 0.005 Lux@F1.8 • True WDR 120dB • Auto focus	• 5MP • 2560x1944@20fps • 0.01 Lux, Smart IR
\$	\$	\$	\$

LWM-MD	LWM-MDB	VPM	CMT	DCM
Wall Mount	Wall Mount	Pole Mount	Corner Mount	In-ceiling Mount
\$	\$	\$	\$	\$

HD-TVI Bullet Camera



Key Features

- High Definition Bullet HD-TVI Camera
 - 2 Matrix IR 2.0 LED up to 65ft
 - 0.01 Lux, Smart IR
- UTC Control to OSD Menu
 - DC 12V

TMB-228MW/TMB-236MW	TMB-528MW
• 2MP • 2.8mm/3.6mm Fixed Lens • 1920×1080P@30fps • True WDR 120dB • IP66	• 5MP • 2.8mm Fixed Lens • 2560x1944@20fps • IP67
\$	\$

HD-TVI Mini Bullet Camerat



Key Features

- High Definition Bullet HD-TVI Camera
 - 3.6mm Fixed Lens
 - 24 IR LEDs up to 65ft
- UTC Contrl to OSD Menu
 - IP66
 - DV 12V

TMB-236RD-(B)
• 2MP • 1920×1080P@30fps • Housing option (White/Black)
\$

UJB-01	UJB-01B
Universal Junction Box	Universal Junction Box
\$	\$

HD-TVI Bullet Camera		
	Key Features • High Definition Bullet HD-TVI Camera • 2 Matrix IR 2.0 LED up to 131ft • 0.01 Lux, Smart IR • UTC Control to OSD Menu • Junction Box Included • DC 12V	
TRB-228MW/TRB-236MW	TRB-528MD-S	
• 2MP • 2.8mm/3.6mm Fixed Lens • 1920×1080P@30fps • 0.01 Lux, Smart IR • True WDR 120dB • IP66	• 5MP Ultra Low Light • 2.8mm Fixed Lens • 2560x1944@20fps • 0.008 Lux@F1.2 • IP67	
\$	\$	
HD-TVI Turret Camera		
	Key Features • High Definition Turret HD-TVI Camera • 2MP • 1920×1080P@30fps • IP66 • DV 12V	TRT-212RD-A(B)
		• 2.8-12mm Varifocal Lens • 36 IR LEDs up to 115ft • CVBS Output (jumper included) • Housing option (White/Black)
		\$
SJ-01	SJ-01B	
		
Junction box	Junction box	
\$	\$	

HD-TVI Bullet Camera

	Key Features • High Definition Bullet HD-TVI Camera • 2.8-12mm Varifocal Lens • 42 IR LEDs up to 165ft • UTC Control to OSD Menu • Junction Box Included • IP66	TRB-212RD(-B) • 2MP • 1920×1080P@30fps • DC 12V, AC 24V • Housing option (White/Black)
		\$
	Key Features • High Definition Bullet HD-TVI Camera • 3.6mm Fixed Lens • 1 Matrix IR LED up to 131ft • UTC Control to OSD Menu • Junction Box Included • IP66	TRB-236MD • 2MP • 1920×1080P@30fps
		\$
	Key Features • High Definition Bullet HD-TVI Camera • 2.8-12mm Varifocal Lens • 1 Matrix IR LED up to 175ft • 3D DNR, ICR, Smart IR • UTC Control to OSD Menu • Junction Box Included • IP66 • DC 12V, AC 24V	TRB-212MW • 2MP • 1920×1080P@30fps • True WDR 120dB • CVBS Output • 0.014 Lux @ (AGC ON), 0 Lux with IR
		\$
	Key Features • High Definition Bullet HD-TVI Camera • 2.8-12mm Varifocal Motorized Lens • 0.01 Lux,Smart IR • UTC Control to OSD Menu • Junction Box Included • DC 12V,AC 24V	TRB-212MW-M • 2MP • 1920×1080P@30fps • True WDR 120dB • 6 Matrix IR LED up to 175ft • IP66
		\$
		TRB-512MW-M • 5MP • 2560x1944@20fps • 2 Matrix IR LED up to 175ft • IP67
		\$

Covert Camera		
		
THC-237	THS-237	THM-237R
● High Definition Covert HD-TVI Camera ● 2MP ● 3.7mm Pinhole Lens ● 1920×1080P@30fps ● DC 12V ● HD-TVI/Analog/AHD/CVI 4-in-1 Toggle ● 1.6"x 1.9"x 1.5" (41mm x 48mm x 38mm)	● High Definition Covert HD-TVI Camera ● 2MP ● 3.7mm Pinhole Lens ● 1920×1080P@30fps ● DC 12V ● HD-TVI/Analog/AHD/CVI 4-in-1 Toggle ● 4.7"x 2.0"x 2.2" (120mm x 59mm x 57mm)	● High Definition Covert HD-TVI Camera ● 2MP ● 3.7mm Pinhole Lens ● 1920X1080@30fps ● IR LEDs up to 50ft, Smart IR ● TVI/AHD/CVI/960H Switchable ● DC 12V
\$	\$	\$

LPR Bullet Camera	Long-range Bullet Camera
TRB-250MW-M	TLP-122LD-M
● High Definition Long-range HD-TVI Camera ● 2MP ● 1920×1080P@30fps ● 5-50mm Varifocal Long-range Lens ● Auto focus ● 2 Matrix IR LEDs up to 360ft ● True WDR 120dB ● CVBS Output ● Junction Box Included ● IP66 ● UTC Control to OSD Menu ● DC 12V, AC 24V 	● High Definition LPR HD-TVI Camera ● 1.3MP ● 1280×960P@30fps ● 6-22mm Varifocal Motorized Lens ● 6 White Giant Flux IR LEDs up to 131ft ● Ultra Low Lux ● 24/7 Color Mode ● Bracket LTB100 Included ● IP66, DC 12V ● CVBS Output 
\$	\$



iSea Group Inc

☎ 1(585)978-3888

✉ Customerservice@iseagroup.org